

THE REZNOR® DIFFERENCE ✓



RHC+

HIGH EFFICIENCY ULTRA LOW
NO_x GAS FIRED HEATING

Product Specification
Quick Guide



FEATURES & BENEFITS



Efficiency

up to 109%
(condensing)



Turndown Ratio

~6:1 (16.67-100%
modulation)



NO_x Emissions

Ultra-low
(<30mg/kWh)



Modular Design

To allow for AHU
modifications



Controls

0-10 V DC, BMS
integration, modbus
& microprocessor



Installation

Vertical/horizontal,
stackable, modular,
AHU, rooftop and
duct on/off modules



Heat Exchanger

Drum & tube
4-pass, stainless
steel 304 and sealed
combustion



Warranty

2-year professional
support, CE-certified,
ErP compliant

Reznor's RHC+ represents the newest evolution in high-performance heat module technology.

Its modular architecture allows seamless integration across a broad range of system configurations, making it well-suited for retrofit applications where existing units need to be replaced.

Designed as a next-generation heating platform, the RHC+ is optimised for installation within ducted systems and supports demanding industrial processes such as drying, curing, and other controlled-temperature environments.

Model Range

Output Range – 10-1,000 kW

RHC+ WMIV –
Slimline Heat Module

RHC+ WMI –
Condensing Heat Module

RHC+ WMIV RS –
Room Sealed Slimline
Heat Module

RHC+ WMI EXT –
Condensing External Heat Module

Our Gas Safe registered engineers are fully equipped to support your service and maintenance needs - wherever you're working.

GET SUPPORT >

Looking for more product information?

View and download technical data below.

VIEW PRODUCT GUIDE >



t. +(44) 0 1384 489700
e. reznorsales@nortek.com
w. reznor.co.uk

Nortek Global HVAC UK
Fens Pool Avenue, Brierley Hill
West Midlands DY5 1QA
United Kingdom

